



## HM-300/350/400

The perfect lightweight and compact selection for your PV system

### Highlights

- Easy installation, just plug and play
- External antenna for stronger communication with DTU
- Power factor (adjustable) 0.8 leading.....0.8 lagging
- Compliant with VDE-AR-N 4105: 2018 & EN50549-1: 2019
- High reliability; NEMA (IP67) enclosure; 6000V surge protection

**Safer****Smarter****More Powerful****More Reliable**

Model	HM-300	HM-350	HM-400
<b>Input Data (DC)</b>			
Commonly used module power (W)	240~380	280~440	320~500
Module compatibility	60-cell or 72-cell PV modules	60-cell or 72-cell PV modules	60-cell or 72-cell PV modules
Peak power MPPT voltage range (V)	29~48	33~48	34~48
Start-up voltage (V)	22	22	22
Operating voltage range (V)	16~60	16-60	16~60
Maximum input voltage (V)	60	60	60
Maximum input current (A)	11.5	11.5	12.5
<b>Output Data (AC)</b>			
Rated output power (VA)	300	350	400
Rated output current(A)	1.36 / 1.30 / 1.25	1.59 / 1.52 / 1.46	1.82 / 1.74 / 1.67
Nominal output voltage (V)	220 / 230 / 240	220 / 230 / 240	220 / 230 / 240
Nominal output voltage range (V)	180-275 <sup>1</sup>	180-275 <sup>1</sup>	180-275 <sup>1</sup>
Nominal frequency/range (V)	50/45-55 <sup>1</sup> or 60/55-65 <sup>1</sup>	50/45-55 <sup>1</sup> or 60/55-65 <sup>1</sup>	50/45-55 <sup>1</sup> or 60/55-65 <sup>1</sup>
Power factor (adjustable)	>0.99 default 0.8 leading...0.8 lagging	>0.99 default 0.8 leading...0.8 lagging	>0.99 default 0.8 leading...0.8 lagging
Total harmonic distortion	<3%	<3%	<3%
Maximum units per branch <sup>2</sup>	16 / 16 / 16	14 / 14 / 14	12 / 12 / 12
<b>Efficiency</b>			
CEC peak efficiency	96.70%	96.70%	96.70%
CEC weighted efficiency	96.50%	96.50%	96.50%
Nominal MPPT efficiency	99.80%	99.80%	99.80%
Nighttime power consumption (mW)	<50	<50	<50
<b>Mechanical Data</b>			
Ambient temperature range (°C)	-40~+65		
Dimensions (W×H×D mm)	182 x 164 x 29.5		
Weight (kg)	1.98		
Enclosure rating	Outdoor-NEMA (IP67)		
Cooling	Natural convection – No fans		
<b>Features</b>			
Communication	2.4GHz Proprietary RF(Nordic)		
Monitoring	Hoymiles Monitoring System		
Compliance	VDE-R-N 4105: 2018, EN 50549-1: 2019, VFR 2019, IEC/EN 62109-1/-2, IEC/EN 61000-6-1/-2/-3/-4, IEC/EN 61000-3-2/-3		

<sup>1</sup> Nominal voltage/frequency range can be changed due to the requirements of local power department.

<sup>2</sup> Refer to local requirements for exact number of microinverters per branch.

### High Reliability Based on World's Top Supplier Partners

