




## MI-1000/1200/1500

New Product Release  
Unique design for 4 PV panels


### Highlights

- Single microinverter connects four PV modules with dual MPPT
- Maximum output power up to 1000/1200/1500W; Adapted to 60 & 72 cells PV panels
- Peak efficiency 96.60%; CEC weighted efficiency 96.50%
- Static MPPT efficiency 99.80%; Dynamic MPPT efficiency 99.76% in overcast weather
- High reliability: NEMA6 (IP67) enclosure; 6000V surge protection



 [sales@hoymiles.com](mailto:sales@hoymiles.com)

 +86-571-28056101

 [www.hoymiles.com](http://www.hoymiles.com)

[info@ralos.fi](mailto:info@ralos.fi) / [www.ralos.eco](http://www.ralos.eco) / 0201552222

Model	MI-1000	MI-1200	MI-1500
-------	---------	---------	---------

**Input Data (DC)**

Commonly used module power (W)	200 ~ 310	240-380	300-470
Peak power MPPT voltage range (V)	27 ~ 48	32-48	36-48
Start-up voltage (V)	22	22	22
Operating voltage range (V)	16-60	16-60	16-60
Maximum input voltage (V)	60	60	60
Maximum input current (A)	10.5	10.5	11.5

**Output Data (AC)**

	@208V AC	@240V AC	@220V AC	@230V AC
Rated output power (W)	1000 / 1200 / 1500	1000 / 1200 / 1500	1000 / 1200 / 1500	1000 / 1200 / 1500
Rated output current (A)	4.81 / 5.77 / 7.21	4.17 / 5 / 6.25	4.54 / 5.45 / 6.81	4.35 / 5.21 / 6.52
Nominal output voltage/range (V)	208/180-275	240/180-275	220/180-275	230/180-275
Nominal frequency/range (Hz)	60/55-65	60/55-65	50/45-55 or 60/55-45	55/45-55
Power factor	>0.99	>0.99	>0.99	>0.99
Total harmonic distortion	<3% / <3% / <5%	<3% / <3% / <5%	<3% / <3% / <5%	<3% / <3% / <5%
Maximum units per branch	4 / 4 / 3	5 / 4 / 3	5 / 4 / 3	5 / 4 / 3

**Efficiency**

CEC peak efficiency	96.70%	96.60%	96.60%
CEC weighted efficiency	96.50%	96.50%	96.50%
Nominal MPPT efficiency	99.80%	99.80%	99.80%
Nighttime power consumption (mW)	<50	<50	<50

**Mechanical Data**

Ambient temperature range (°C)	-40~+65
Dimensions (W×H×D mm)	280x176x33
Weight (kG)	3.75 (including 2.32m AC cable)
Enclosure rating	Outdoor-NEMA (IP67)
Cooling	Natural convection – No fans

**Features**

Communication	2.4G RF
Monitoring	Hoymiles monitoring system
Design lifetime	>25 years

**High Reliability Based on World's Top Supplier Partners**
